

GB SWING CHECK VALVE
(WCB, CF8, CF8M, TI, NI)

国标止回阀


旋启式国标止回阀
(GB, ANSI, JIS, DIN, BS)
GB Swing Check Valve



旋启式



升降式



主要尺寸及重量 Main size and weight

公称压力 Nominal pressure PN/MPa	DN(mm)	尺寸 Dimensions (mm)						
		L	D	D1	D2	b-f	z-φd	H
1.6	25	160	115	85	65	14-2	4-φ14	115
	32	180	135	100	78	16-2	4-φ18	120
	40	200	145	110	85	16-3	4-φ18	130
	50	230	160	125	100	16-3	4-φ18	140
	65	290	180	145	120	18-3	4-φ18	150
	80	310	195	160	135	20-3	8-φ18	170
	100	350	215	180	155	20-3	8-φ18	185
	125	400	245	210	185	22-3	8-φ18	195
	150	480	280	240	210	24-3	8-φ23	225
	200	600	335	295	265	26-3	12-φ23	250
	250	650	405	355	320	30-3	12-φ25	270
	300	750	460	410	375	30-3	12-φ25	300
2.5	25	160	115	85	65	16-2	4-φ14	115
	32	180	135	100	78	16-2	4-φ18	120
	40	200	145	110	85	18-3	4-φ18	130
	50	230	160	125	100	20-3	4-φ18	140
	65	250	180	145	125	22-3	8-φ18	150
	80	310	195	160	135	22-3	8-φ18	170
	100	350	230	190	160	24-3	8-φ23	185
	125	400	270	220	188	28-3	8-φ25	195
	150	480	300	250	218	30-3	8-φ25	225
	200	600	360	310	278	34-3	12-φ25	250
	250	650	425	370	335	36-3	12-φ30	270
	300	750	485	430	390	40-4	16-φ30	300

设计制造标准 Design & Manufacture Standard

设计与制造按GB/T 12236、GB/T 12235
结构长度按GB/T 12221
法兰连接尺寸按JB/T 79
检验按JB/T 9002

Design and manufacture as GB/T 12236、GB/T 12235
Face to face dimensions as GB/T 12221
End flange dimension as JB/T 79
Pressure test as JB/T 9002