


AMERICAN TYPE FEMALE GLOBE VALVE  
 (WCB, CF8, CF8M)

## 美式内螺纹截止阀

## 美式内螺纹截止阀

 American Type Female  
 Globe Valve

J11W-(16-64)C、P、R



## 主要零件材料 Materials of main parts

零件名称 Description of Parts	J11H-(16-64)C	J11W-(16-64)P	J11W-(16-64)R
阀体 Body	WCB	ZG1Cr18Ni9Ti CF8	ZG1Cr18Ni12Mo2Ti CF8M
阀盖 Bonnet	WCB	ZG1Cr18Ni9Ti CF8	ZG1Cr18Ni12Mo2Ti CF8M
阀瓣 Disc	ZG1Cr18Ni9Ti CF8	ZG1Cr18Ni9Ti CF8	ZG1Cr18Ni12Mo2Ti CF8M
阀杆 Stem	1Cr18Ni9Ti 304	1Cr18Ni9Ti 304	1Cr18Ni12Mo2Ti 316
密封 Sealing		304,316	
填料 Packing	聚四氟乙烯 Poly(tetrafluorethylene)(PTFE)		

## 主要外形尺寸 Main outer size

DN	G	L	E	B	H	W
8	1/4"	65	15	23	80	70
10	3/8"	65	15	26	80	70
15	1/2"	65	16	31	88	70
20	3/4"	75	18	38	95	70
25	1"	90	20	46	110	80
32	1 1/4"	105	21.5	56	123	100
40	1 1/2"	120	23	63	135	100
50	2"	140	24.5	76	150	100
65	2 1/2"	152	27	89	190	120
80	3"	175	30	104	210	140

## 性能规范 Specifications

公称压力: PN1.6,2.5,4.0,6.4MPa  
 强度试验压力: PT2.4,3.8,6.0,9.6MPa  
 高压密封试验压力: 1.8,2.8,4.4,7.1MPa  
 适用介质: J11H-(16-64)C 水、油品、气  
 适用温度: -29~180°C  
 适用介质: J11W-(16-64)P 硝酸类  
 J11W-(16-64)R 醋酸类

Nominal pressure: PN1.6,2.5,4.0,6.4MPa  
 Strength testing pressure: PT2.4,3.8,6.0,9.6MPa  
 Seat testing pressure (high pressure): 1.8,2.8,4.4,7.1MPa  
 Applicable media:  
 J11H-(16-64)C Water,Oil,Gas  
 Applicable temperature: -29~180°C  
 Applicable media:  
 J11W-(16-64)P Nitric acid  
 J11W-(16-64)R Acetic acid