





OVERVIEW BROCHURE

ISO9001 CE RoHS   



Official website: <http://www.covnagroup.com/>

Alibaba website: <https://automatic.en.alibaba.com/>

Name: Echo

E-mail: sales@covnagroup.com

Whatsapp/Facebook/Linkedin/Mobile: 86-15622261856

COVNA GROUP CO.,LTD

科威納 COVNA®
— VALVE —



CE ISO 9001 RoHS TÜV

Specialized Fluid Control Valve Manufacture



Stainless Steel Thread Solenoid Valve
2W21



Stainless Steel Flanged Solenoid Valve
2W21-F



Stainless Steel Solenoid Valve
2W31-S



Brass Solenoid Valve
2W31



Stainless Steel Solenoid Valve
HK02-S



Brass Automatic Drain Solenoid Valve
HK11-2



Stainless Steel Drain Solenoid Valve
HK11-4



Brass Solenoid Valve
2W



Stainless Steel Flanged Solenoid Valve
2W-F-S



Stainless Steel Solenoid Valve
HKP



Brass Thread Solenoid Valve
HK07



Brass Flanged Solenoid Valve
HK07-F



Pulse Valve
DMF-Z



High Temperature Solenoid Valve
HK10



Direct Acting Water Purifier Solenoid Valve
HKW1



High Frequency Solenoid Valve
HKSY



5/2 Reversing Solenoid Valve
4V210



5/2 Ex-Proof Solenoid Valve
4V220-EX



3/2 Ex-Proof Solenoid Valve
3V210-EX



Mechanical Valve
4R210

Water Solenoid Valve



Specifications

- 【Model】 2W31
- 【Structure】 Diaphragm
- 【Size Range】 DN15 to DN50, 1/2" to 2"
- 【Operating Pressure】 0 to 1.0MPa (0 to 150PSI)
- 【Valve Operation Type】 Normally Closed (NC)
- 【Number of Ways】 2/2 Valve, Two Way Two Position
- 【Body Materials】 Brass, Stainless Steel, Plastic Body
- 【Sealing Materials】 NBR, EPDM, FKM (VITON), PTFE (TEFLON)

Water Solenoid Valve



Specifications

- 【Model】 HK07
- 【Structure】 Pilot
- 【Size Range】 DN15 to DN50, 1/2" to 2"
- 【Operating Pressure】 0.03 to 1.0MPa (4.35 to 150PSI)
- 【Valve Operation Type】 Normally Closed (NC)
- 【Number of Ways】 2/2 Valve, Two Way Two Position
- 【Body Materials】 Brass, Stainless Steel
- 【Sealing Materials】 NBR, EPDM, FKM (VITON), PTFE (TEFLON)

Water Solenoid Valve



Specifications

- 【Model】 HK02
- 【Structure】 Direct Acting
- 【Size Range】 DN06 to DN15, 1/8" to 1/2"
- 【Operating Pressure】 0 to 1.6MPa (0 to 250PSI)
- 【Valve Operation Type】 Normally Closed (NC)
- 【Number of Ways】 2/2 Valve, Two Way Two Position
- 【Body Materials】 Brass, Stainless Steel, Plastic Body
- 【Sealing Materials】 NBR, EPDM, FKM (VITON), PTFE (TEFLON)

Gas Solenoid Valve



Specifications

- 【Model】 ZCM
- 【Structure】 Diaphragm
- 【Size Range】 DN15 to DN50, 1/2" to 2"
- 【Operating Pressure】 0 to 0.4MPa (0 to 50PSI)
- 【Valve Operation Type】 Normally Closed (NC)
- 【Number of Ways】 2/2 Valve, Two Way Two Position
- 【Body Materials】 Brass
- 【Sealing Materials】 NBR

3 Way Solenoid Valve



Specifications

- 【Model】 VX31
- 【Structure】 Diaphragm
- 【Size Range】 DN06 to DN08, 1/8" to 1/4"
- 【Operating Pressure】 0 to 1.0MPa (0 to 150PSI)
- 【Valve Operation Type】 Normally Closed (NC)
- 【Number of Ways】 3/2 Valve, Three Way Two Position
- 【Body Materials】 Brass
- 【Sealing Materials】 NBR, EPDM, FKM (VITON)

Steam Solenoid Valve



Specifications

- 【Model】 US
- 【Structure】 Pilot
- 【Size Range】 DN15 to DN50, 1/2" to 2"
- 【Operating Pressure】 0.03 to 1.6MPa (4.35 to 250PSI)
- 【Valve Operation Type】 Normally Closed (NC)
- 【Number of Ways】 2/2 Valve, Two Way Two Position
- 【Body Materials】 Brass, Stainless Steel
- 【Sealing Materials】 FKM (VITON), PTFE (TEFLON)

Steam Solenoid Valve



Specifications

- 【Model】 ZCZ
- 【Structure】 Pilot
- 【Size Range】 DN15 to DN50, 1/2" to 2"
- 【Operating Pressure】 0.03 to 1.0MPa (4.35 to 150PSI)
- 【Valve Operation Type】 Normally Closed (NC)
- 【Number of Ways】 2/2 Valve, Two Way Two Position
- 【Body Materials】 Brass
- 【Sealing Materials】 FKM (VITON), PTFE (TEFLON)

Hot Water and Steam Solenoid Valve



Specifications

- 【Model】 HKB21
- 【Structure】 Pilot
- 【Size Range】 DN10 to DN25, 3/8" to 1"
- 【Operating Pressure】 0.03 to 1.0MPa (4.35 to 150PSI)
- 【Valve Operation Type】 Normally Closed (NC)
- 【Number of Ways】 2/2 Valve, Two Way Two Position
- 【Body Materials】 Brass, Stainless Steel
- 【Sealing Materials】 NBR, EPDM, FKM (VITON), PTFE (TEFLON)

Auto Drain Solenoid Valve



Specifications

- 【Model】 HK11-2
- 【Structure】 Direct Acting
- 【Size Range】 DN10 to DN25, 3/8" to 1"
- 【Operating Pressure】 0 to 1.0MPa (0 to 150PSI)
- 【Valve Operation Type】 Normally Closed (NC)
- 【Number of Ways】 2/2 Valve, Two Way Two Position
- 【Body Materials】 Brass,
- 【Sealing Materials】 NBR, EPDM, FKM (VITON), PTFE (TEFLON)

HK10 Solenoid Valve



Specifications

- 【Model】 HK10
- 【Structure】 Pilot
- 【Size Range】 DN10 to DN50, 3/8" to 2"
- 【Operating Pressure】 0.05 to 1.6MPa (5 to 250PSI)
- 【Valve Operation Type】 Normally Closed (NC)
- 【Number of Ways】 2/2 Valve, Two Way Two Position
- 【Body Materials】 Brass, Stainless Steel
- 【Sealing Materials】 PTFE (TEFLON)

High Pressure Solenoid Valve



Specifications

- 【Model】 HKKB
- 【Structure】 Pilot
- 【Size Range】 DN06 to DN10, 1/8" to 3/8"
- 【Operating Pressure】 0 to 25MPa (0 to 3600PSI)
- 【Valve Operation Type】 Normally Closed (NC)
- 【Number of Ways】 2/2 Valve, Two Way Two Position
- 【Body Materials】 Brass, Stainless Steel
- 【Sealing Materials】 PTFE (TEFLON)

Anti-Corrosion Solenoid Valve



Specifications

- 【Model】 HKFP21
- 【Structure】 Pilot
- 【Size Range】 DN06 to DN25, 1/8" to 1"
- 【Operating Pressure】 0 to 0.15MPa (0 to 25PSI)
- 【Valve Operation Type】 Normally Closed (NC)
- 【Number of Ways】 2/2 Valve, Two Way Two Position
- 【Body Materials】 PTFE (TEFLON)
- 【Sealing Materials】 PTFE (TEFLON)