





OVERVIEW BROCHURE

ISO9001 CE RoHS   



Official website: <http://www.covnagroup.com/>

Alibaba website: <https://automatic.en.alibaba.com/>

Name: Echo

E-mail: sales@covnagroup.com

Whatsapp/Facebook/Linkedin/Mobile: 86-15622261856

COVNA GROUP CO.,LTD



科威納 COVNA[®]
— VALVE —



CE ISO 9001 RoHS TÜV

Specialized Fluid Control Valve Manufacture



Cast Iron Motorized Butterfly Valve with PTFE Sealing
HK-60D



Cast Iron Motorized Butterfly Valve with NBR Sealing
HK-60D-1



Motorized Lug Butterfly Valve
HK-60D-2



Stainless Steel Motorized Butterfly Valve
HK-60D-3



UPVC Motorized Butterfly Valve
HK-60D-7



Motorized 3PCS 2 way thread Ball Valve
HK-60Q



Motorized 3 way thread Ball Valve
HK-60Q-T



Motorized 2 way Flanged Ball Valve
HK-60Q-F



Motorized 3 way Flanged Ball Valve
HK-60Q-F-T



Motorized Thin Ball Valve
HK-60Q-54



2 Way Sanitary Motorized Ball Valve
HK-60Q-W



3 Way Sanitary Motorized Ball Valve
HK-60Q-W-T



2 Way UPVC Motorized Ball Valve
HK-60Q-V



3 Way UPVC Motorized Ball Valve
HK-60Q-V-T



Sanitary Motorized Butterfly Valve
HK-60D-W



Stainless Steel 2 Way Thread Motorized Ball Valve



Stainless Steel 2 Way Thread Motorized Ball Valve



Brass 2 Way Thread Motorized Ball Valve



Brass 2 Way Thread Motorized Ball Valve



Brass 2 Way Thread Motorized Ball Valve With Manual device



Stainless Steel 3 Way Thread Motorized Ball Valve



Stainless Steel 3 Way Thread Motorized Ball Valve



Brass 3 Way Thread Motorized Ball Valve



Brass 3 Way Thread Motorized Ball Valve



PVC 2 Way Thread Motorized Ball Valve



PVC 2 Way Thread Motorized Ball Valve



Brass 2 Way Thread Motorized Ball Valve For air conditioner



Brass 3 Way Thread Motorized Ball Valve For air conditioner



Timing Stainless Steel 2 Way Thread Motorized Ball Valve



Timing Stainless Steel 2 Way Thread Motorized Ball Valve



Thin Regulating Motorized Ball Valve



Motorized 2 PCS Ball Valve



Motorized Butterfly Valve with Hard Sealing



Motorized Butterfly Valve with PTFE Sealing



EX-Proof 3 Way Motorized Flanged Ball Valve



Sanitary Motorized Butterfly Valve



Sanitary Tri-clamp Motorized Ball Valve



Motorized Vacuum Ball Valve



EX-Proof PVC Motorized Butterfly Valve



EX-Proof Motorized Ball Valve

3PCS Female Thread Motorized Ball Valve



Specifications

【Size Range】 DN10 to DN100, 3/8" to 4"

【Operating Pressure】 1.6 to 6.4MPa

【Body Materials】 WCB, Stainless Steel

【Core Materials】 WCB, Stainless Steel

【Sealing Materials】 PTFE (TEFLON)

【Control Mode】 ON/OFF Type, Modulating Type

Butt Welded Motorized Ball Valve



Specifications

【Size Range】 DN10 to DN100, 3/8" to 4"

【Operating Pressure】 1.6 to 6.4MPa

【Body Materials】 WCB, Stainless Steel

【Core Materials】 WCB, Stainless Steel

【Sealing Materials】 PTFE (TEFLON)

【Control Mode】 ON/OFF Type, Modulating Type

3 Way Female Thread Motorized Ball Valve



Specifications

【Size Range】 DN15 to DN100, 1/2" to 4"

【Operating Pressure】 1.6 to 6.4MPa

【Body Materials】 WCB, Stainless Steel

【Core Materials】 WCB, Stainless Steel

【Sealing Materials】 PTFE (TEFLON)

【Structure】 3 Way T Port, L Port are Available

【Control Mode】 ON/OFF Type, Modulating Type

2 Way Tri-Clamp Motorized Ball Valve



Specifications

- 【Size Range】 DN15 to DN150, 1/2" to 6"
- 【Operating Pressure】 1.6 to 6.4MPa
- 【Body Materials】 Stainless Steel
- 【Disc Materials】 Stainless Steel
- 【Sealing Materials】 EPDM, Silicone Rubber
- 【Control Mode】 ON/OFF Type, Modulating Type

3 Way Sanitary Motorized Ball Valve



Specifications

- 【Size Range】 DN15 to DN150, 1/2" to 6"
- 【Operating Pressure】 1.6 to 6.4MPa
- 【Body Materials】 Stainless Steel
- 【Disc Materials】 Stainless Steel
- 【Sealing Materials】 EPDM, Silicone Rubber
- 【Structure】 3 Way T Port, L Port are Available
- 【Control Mode】 ON/OFF Type, Modulating Type

Motorized Flanged Ball Valve



Specifications

- 【Size Range】 DN15 to DN250, 1/2" to 10"
- 【Operating Pressure】 1.0 to 6.4MPa
- 【Body Materials】 WCB, Stainless Steel
- 【Core Materials】 WCB, Stainless Steel
- 【Stem Materials】 WCB, Stainless Steel
- 【Sealing Materials】 PTFE (TEFLON), Stainless Steel
- 【Control Mode】 ON/OFF Type, Modulating Type

3 Way Motorized Flanged Ball Valve



Specifications

- 【Size Range】 DN15 to DN250, 1/2" to 10"
- 【Operating Pressure】 1.6 to 6.4MPa
- 【Body Materials】 WCB, Stainless Steel
- 【Core Materials】 WCB, Stainless Steel
- 【Sealing Materials】 PTFE (TEFLON), Stainless Steel
- 【Structure】 3 Way T Port, L Port are Available
- 【Control Mode】 ON/OFF Type, Modulating Type

High Pressure Motorized 2Way Ball Valve



Specifications

- 【Size Range】 DN08 to DN50, 1/4" to 2"
- 【Operating Pressure】 10.0 to 40.0MPa
- 【Body Materials】 Stainless Steel
- 【Core Materials】 Stainless Steel
- 【Sealing Materials】 PTFE
- 【Control Mode】 ON/OFF Type, Modulating Type

High Pressure Motorized 3Way Ball Valve



Specifications

- 【Size Range】 DN08 to DN50, 1/4" to 2"
- 【Operating Pressure】 10.0 to 40.0MPa
- 【Body Materials】 Stainless Steel
- 【Core Materials】 Stainless Steel
- 【Sealing Materials】 PTFE
- 【Structure】 3 Way T Port, L Port are Available
- 【Control Mode】 ON/OFF Type, Modulating Type

Plastic 2 Way Motorized Ball Valve



Specifications

【Size Range】 DN15 to DN100, 1/2" to 4"

【Operating Pressure】 1.0MPa

【Body Materials】 CPVC, UPVC

【Disc Materials】 CPVC, UPVC

【Sealing Materials】 PTFE (TEFLON)

【Control Mode】 ON/OFF Type, Modulating Type

Plastic 3 Way Motorized Ball Valve



Specifications

【Size Range】 DN15 to DN50, 1/2" to 2"

【Operating Pressure】 1.0MPa

【Body Materials】 CPVC, UPVC

【Disc Materials】 CPVC, UPVC

【Sealing Materials】 PTFE (TEFLON)

【Structure】 3 Way T Port, L Port are Available

【Control Mode】 ON/OFF Type, Modulating Type

Plastic Motorized Butterfly Valve



Specifications

【Size Range】 DN50 to DN300, 2" to 12"

【Operating Pressure】 1.0MPa

【Body Materials】 CPVC, UPVC

【Disc Materials】 CPVC, UPVC

【Sealing Materials】 PTFE (TEFLON)

【Control Mode】 ON/OFF Type, Modulating Type

Cast Iron Motorized Wafer Butterfly Valve



Specifications

【Size Range】 DN50 to DN600, 2" to 24"

【Operating Pressure】 1.0 to 1.6MPa

【Body Materials】 Cast Iron, Ductile Iron, Stainless Steel

【Disc Materials】 Cast Iron, Stainless Steel

【Sealing Materials】 NBR, EPDM, FKM (VITON), PTFE (TEFLON)

【Control Mode】 ON/OFF Type, Modulating Type

Cast Iron Motorized Lug Butterfly Valve



Specifications

【Size Range】 DN50 to DN600, 2" to 24"

【Operating Pressure】 1.0 to 1.6MPa

【Body Materials】 Cast Iron, Ductile Iron, Stainless Steel

【Disc Materials】 Cast Iron, Stainless Steel

【Sealing Materials】 NBR, EPDM, FKM (VITON), PTFE (TEFLON)

【Control Mode】 ON/OFF Type, Modulating Type

Stainless Steel Motorized Wafer Butterfly Valve



Specifications

【Size Range】 DN50 to DN600, 2" to 24"

【Operating Pressure】 1.0 to 1.6MPa

【Body Materials】 Cast Iron, Ductile Iron, Stainless Steel

【Disc Materials】 Cast Iron, Stainless Steel

【Sealing Materials】 NBR, EPDM, FKM (VITON), PTFE (TEFLON)

【Control Mode】 ON/OFF Type, Modulating Type

Aluminum Motorized Lugless Butterfly Valve



Specifications

【Size Range】 DN50 to DN600, 2" to 24"

【Operating Pressure】 1.0 to 1.6MPa

【Body Materials】 Ductile Iron, Aluminum, Stainless Steel

【Disc Materials】 Stainless Steel

【Sealing Materials】 EPDM, PTFE (TEFLON)

【Control Mode】 ON/OFF Type, Modulating Type

Metal Sealed Motorized Wafer Butterfly Valve



Specifications

【Size Range】 DN50 to DN600, 2" to 24"

【Operating Pressure】 1.0 to 1.6MPa

【Body Materials】 WCB, Stainless Steel

【Disc Materials】 WCB, Stainless Steel

【Stem Materials】 WCB, Stainless Steel

【Sealing Materials】 PTFE (TEFLON), Stainless Steel

【Control Mode】 ON/OFF Type, Modulating Type

Metal Sealed Motorized Flanged Butterfly Valve



Specifications

【Size Range】 DN50 to DN600, 2" to 24"

【Operating Pressure】 1.0 to 1.6MPa

【Body Materials】 Ductile Iron, WCB, Stainless Steel

【Disc Materials】 Ductile Iron, WCB, Stainless Steel

【Stem Materials】 WCB, Stainless Steel

【Sealing Materials】 PTFE (TEFLON), Stainless Steel

【Control Mode】 ON/OFF Type, Modulating Type

Motorized Flanged Butterfly Valve



Specifications

- 【Size Range】 DN50 to DN600, 2" to 24"
- 【Operating Pressure】 1.0 to 1.6MPa
- 【Body Materials】 Ductile Iron, WCB, Stainless Steel
- 【Disc Materials】 Ductile Iron, WCB, Stainless Steel
- 【Stem Materials】 WCB, Stainless Steel
- 【Sealing Materials】 EPDM, PTFE
- 【Control Mode】 ON/OFF Type, Modulating Type

Electric Fluorines Lined Butterfly Valve



Specifications

- 【Size Range】 DN50 to DN600, 2" to 24"
- 【Operating Pressure】 1.0 to 1.6MPa
- 【Body Materials】 Cast Iron, Ductile Iron, Stainless Steel
- 【Disc Materials】 Cast Iron, Stainless Steel
- 【Sealing Materials】 PTFE (TEFLON)
- 【Control Mode】 ON/OFF Type, Modulating Type

Motorized Sanitary Butterfly Valve



Specifications

- 【Size Range】 DN15 to DN150, 1/2" to 6"
- 【Operating Pressure】 0.6 to 1.6MPa
- 【Body Materials】 Stainless Steel
- 【Disc Materials】 Stainless Steel
- 【Sealing Materials】 EPDM, Silicone Rubber
- 【Control Mode】 ON/OFF Type, Modulating Type

Ex-proof Soft Sealed Motorized Butterfly Valve



Specifications

【Size Range】 DN50 to DN800, 2" to 32"

【Operating Pressure】 1.0 to 1.6MPa

【Body Materials】 Cast Iron, Ductile Iron, WCB, Stainless Steel

【Disc Materials】 Ductile Iron, Stainless Steel

【Stem Materials】 WCB, Stainless Steel

【Sealing Materials】 NBR, EPDM, FKM (VITON), PTFE (TEFLON)

【Control Mode】 ON/OFF Type, Modulating Type

Ex-proof Metal Sealed Motorized Butterfly Valve



Specifications

【Size Range】 DN50 to DN600, 2" to 24"

【Operating Pressure】 1.0 to 1.6MPa

【Body Materials】 WCB, Stainless Steel

【Disc Materials】 WCB, Stainless Steel

【Stem Materials】 WCB, Stainless Steel

【Sealing Materials】 PTFE (TEFLON), Stainless Steel

【Control Mode】 ON/OFF Type, Modulating Type

Ex-proof Plastic Motorized Butterfly Valve



Specifications

【Size Range】 DN50 to DN300, 2" to 12"

【Operating Pressure】 0.6 to 1.6MPa

【Body Materials】 UPVC

【Disc Materials】 UPVC

【Sealing Materials】 NBR, EPDM, FKM (VITON), PTFE (TEFLON)

【Control Mode】 ON/OFF Type, Modulating Type

Ex-proof Soft Sealed Motorized Flanged Butterfly Valve



Specifications

【Size Range】 DN50 to DN700, 2" to 28"

【Operating Pressure】 1.0 to 1.6MPa

【Body Materials】 Ductile Iron, WCB, Stainless Steel

【Disc Materials】 Cast Iron, Ductile Iron, WCB, Stainless Steel

【Stem Materials】 WCB, Stainless Steel

【Sealing Materials】 EPDM, PTFE (TEFLON)

【Control Mode】 ON/OFF Type, Modulating Type

Ex-proof Metal Sealed Motorized Flange Butterfly Valve



Specifications

【Size Range】 DN40 to DN600, 2" to 24"

【Operating Pressure】 1.0 to 1.6MPa

【Body Materials】 Ductile Iron, WCB, Stainless Steel

【Disc Materials】 Ductile Iron, WCB, Stainless Steel

【Stem Materials】 WCB, Stainless Steel

【Sealing Materials】 EPDM, PTFE (TEFLON)

【Control Mode】 ON/OFF Type, Modulating Type